



## Idromix

ST4-0217

*Power additive to be mixed with dry cement and aggregates for casting foundations, concrete tanks and water systems to improve water resistance*

### DESCRIPTION

**Idromix** is a powder additive which can be added to mortars and concrete providing a significant water repellent quality in mass against water penetration. The product does not alter the times of the beginning and end of setting; it is completely free of chlorides and therefore it does not harm reinforcement rods and the equipment it comes into contact with.

### USES

Idromix is used as an additive for casting concrete foundation walls, dams, swimming pools, tanks, reservoirs, canals and all structures which must contain or exclude water. It is also used as an additive for mortars on walls exposed to beating rain, on structures below ground level etc.

The product is compatible with all Portland, Pozzolanic and blast furnace cements: It is also compatible with other Kimia concrete additives. Each additive must be added separately to the mixture.

### APPLICATION

**Idromix** must be added when dry to the mortar or concrete.

### CONSUMPTION

1-2 % of the cement weight (1-2 kg per 100 kg of cement).

### PACKAGING

Sac. 10 Kg – Pallet 30x10 – 600 Kg

### STORAGE

Idromix should be kept away from moisture. Store in a dry and sheltered place. In these conditions and in sealed containers the product's stability is 12 months.

### WARNING

Product intended for professional use.

The technical specifications and application methods recommended herein are based on our current knowledge and experience and do not represent any form of guarantee of the final results obtainable with the product.

It is the customer's responsibility to check that the product is suitable for the intended use and that this data sheet is still effective and has not been replaced with a more recent version.