



Kimitech 120

ST7-0217

Pre-primed, alkali-resistant polypropylene reinforcing fabric for waterproofing and protective cycles

DESCRIPTION

Kimitech 120 is an elastic, polypropylene-based reinforcing mesh.

Highly resistant even in alkaline environments and ageing processes, maintaining durable its own characteristics in terms of elasticity and mechanical resistance.

USES

Kimitech 120 is a product used as reinforcing mesh for waterproofing cycles involving **Betonfix** and **Kimicover** products:

- treatment of wall-floor joints with waterproofing products;
- treatment of joints using **Kimicover JOINT e Kimicover JOINT P**.

APPLICATION

For intended uses please see the TDS of correlated products.

PACKAGING

Rolls:

- 100 cm width, 50 m length;
- 25 cm width, 50 m length.

WARNING

Product for professional use.

The technical specifications and application methods recommended herein are based on our current knowledge and experience and do not represent any form of guarantee of the final results obtainable with the product.

It is the customer's responsibility to check that this data sheet is still effective and has not been replaced with a more recent version, and that the product is suitable for the intended use.

Charactersitics	Typical data
Elongation at failure (warp)	28 %
Elongation at failure (tweft)	20 %
Colour	White
Weigth	87 g/m ²
Tensile resistance load (warp)	350 N/50 mm
Tensile resistance load (weft)	660 N/50 mm
Tensile resistance load after ageing treatment (warp)	350 N/50 mm
Tensile resistance load after ageing treatment (warp)	660 N/50 mm