

Kimitech B2

ST12-0319



Synthetic resin to improve chemical and mechanical characteristics, reducing elastic module, of mortars

DESCRIPTION

Kimitech B2 is a specific latex capable to improve chemical and mechanical characteristics, involving also adhesion to the support, of mortars included in **Limepor**, **Tectoria**, **Basic** and **Betonfix** ranges.

USES

Kimitech B2 can be used in combination with **Limepor IZ4**, to better restore detached frescoed plasters; if it is used in combination with mortars of **Betonfix**, **Limepor**, **Basic** and **Tectoria** ranges, the product helps the inorganic matrix improving its own adhesion power to the existing support: very useful in case of preparation of preliminary layers before application of composite reinforcing systems and in case of reconstruction of damaged stones or brick elements.

APPLICATION

Kimitech B2 can be used in place of water in the mix of the mortar (ratios of mixing remain exactly the same indicated in the technical data sheet of the specific mortar).

PACKAGING

Tap 25 Kg – pallet 24x25 – 600 Kg

STORAGE

Protect the product from frost. Store the product at temperatures above +5°C. In these conditions and in air/watertight containers, the product remains stable for 24 months.

WARNING

Product for professional use.

The equipment used to lay the product must be washed with water before hardening.

The technical specifications and application methods recommended herein are based on our current knowledge and experience and do not represent any form of guarantee of the final results obtainable with the product.

It is the customer's responsibility to check that this data sheet is still effective and has not been replaced with a more recent version, and that the product is suitable for the intended use.

Characteristics	Typical data
Consistency	Liquid
Colour	White
Density EN ISO 2811 - 1	1,03 g/cm ³
pH UNI 8311	9 - 10
Solid content UNI 8309	22 %
Brookfield viscosity (300 r.p.m. and 25°C) UNI 8490-3	1 - 10 mPa·s