



Soluzione P

ST5-0319

Buffered acid-base chemical formulation for cleaning brick facades and industrial flooring

DESCRIPTION

Soluzione P is a single component, ready to use formula with a base of buffer acids. It is used in the building trade as a chemical treatment to eliminate cement mortar residues.

USES

Soluzione P is used to eliminate cement-based mortar residues for both ceramic or terracotta floors and coverings, to chemically roughen industrial floors finished with quartz powder in the case of successive colored coverings and to eliminate salt marks on concrete surfaces.

APPLICATION



Roll or brush



Keep on the surface for 2-3 mins

Soluzione P It must be applied either with a brush, roller or a single brush and kept on the surface for 2-3 minutes, then wash the surface with abundant water. If significant traces to be removed are still present, after the first application, repeat the operation until all the residues have been eliminated. Avoid to apply the product directly on metals and delicate materials

CONSUMPTION

0,3 Kg/m²

PACKAGING

- Tan. 5 lt box 4 x 5 lt
 Pallet 96x5 lt (24 boxes) 480 lt.
- Tan. 25 lt.
 Pallet 24x25 lt 600 lt.

STORAGE

Keep away from freezing temperatures; do not store at a temperature below + 5° C. In its sealed container the product maintains its stability for 24 months.

Characteristics	Values
Appearance	Blue liquid
Specific weight	1,05 ± 0,05 Kg/l
рН	4 ± 0,5

WARNING

This product is intended for professional use.

The development of vapors associated with the use of the **Soluzione P** is a function of the quantities of product used which, in turn, depend on the extension, type and condition of maintenance of the treated surface and the type of organic/inorganic materials deposited on the substrate and the' final effect you want.

Ensure adequate air circulation to protect the health of applicators.

Avoid direct contact with metal and soft materials with acid. The product should be handled with caution: use gloves, goggles and protective creams to prevent contact with skin and eyes.

Equipment used for product preparation and placing must be cleaned with water before hardening.

The technical specifications and application methods recommended herein are based on our current knowledge and experience and do not represent any form of guarantee of the final results obtainable with the product.

It is the customer's responsibility to check that this data sheet is still effective and has not been replaced with a more recent version, and that the product is suitable for the intended use